

Lithium Iron Phosphate (LiFePO4) Battery

MBL12-70DIN

12.8V70AH

896Wh

Features of LiFePO4 Battery

Longer Cycle Life

LiFePO4 batteries have a cycle life five times higher than that of SLA batteries

High Power & Light weight

LiFePO4 batteries have twice the power of SLA batteries, while half the weight, helpful for transport and installation

Intelligent management control


Intelligent BMS system covered by LFP batteries to ensure that batteries work on safety and perfect condition

Lower Self-discharge rate

Lower Self-discharge rate to guarantee LFP batteries be stored more longer than SLA batteries



Physical Dimension



Applications

- Caravan, RV, camping
- UPS (replacement of SLA batteries)
- Marine, golf cart
- Solar, wind system
- PV, solar light

Electrical Characteristics

Chemistry	LiFePO4
Nominal Voltage	12.8V
Nominal Capacity	70Ah (C5,25°C)
Energy	896Wh
Internal Resistance	≤10 mΩ
Cycle Life	>3500 cycles @1C 70%DOD
Months Self Discharge	<3%
Efficiency of Charge	100% @0.5C
Efficiency of Discharge	96-99% @1C

Standard Charge

Charge Voltage	14.6±0.2V
Charge Mode	0.2C to 14.6V, then 14.6V charge current to 0.02C (CC/CV)
Charger Current	40A
Max. Charge Current	80A
Charge Cut-off Voltage	14.6V±0.2V

Standard Discharge

Rated Discharge Current	40A
Max Discharge Current	80A
Max. Pulse Current	240A(<3s)
Discharge Cut-off Voltage	10V
Charge Temperature	0 °C to 45 °C (32Fto 113F) @60±25% Relative Humidity
Discharge Temperature	-20 °C to 60 °C (-4F to 140F) @60±25% Relative Humidity
Storage Temperature	0 °C to 40 °C (32Fto 104F) @60±25% Relative Humidity
Water Dust Resistance	IP65

Mechanical

BMS	4S/4P
Plastic Case	ABS (DIN case)
Dimensions (in./mm.)	276x175x190 mm
Weight (lbs./kg.)	7.5kg(16.53lbs)
Terminal	SAE


Lithium Iron Phosphate (LiFePO4) Battery

MBL12-70DIN


12.8V70AH

896Wh


Different Rate Discharge Curve (25°C)




Different Temperature Discharge Curve(0.5C)




State of Charge Curve (0.5C, 25°C)



Charging Characteristics(0.5C, 25°C)



Different DOD Discharge Cycle Life Curve(1C)



Different Temperature Self Discharge Curve

