Lithium Iron Phosphate (LiFePO4) Battery		
MBL24-105C		25.6V105AH 2688Wh
Features of LiFePO4 Battery		
Longer Cycle Life LiFePO4 batteries have a cycle live five times higher than that of SLA batteries High Power & Light weight LiFePO4 batteries have twice the power of SLA batteries, while half the weight, helpful for transport and installation Intelligent management control Intelligent BMS system covered by LFP batteries to ensure that batteries work on safety and perfect condition Lower Self-discharge rate Lower Self-discharge rate to guarantee LFP batteries be stored more longer than SLA batteries		Transformer Trans
Physical Dimension		Applications
		● Caravan, RV, camping
		 UPS (replacement of SLA batteries) Marine, golf cart Solar, wind system PV, solar light
Electrical Characteristics	Chemistry	LiFePO4
	Nominal Voltage	25.6V
	Nominal Capacity	105Ah (C5,25°C)
	Energy	2688Wh
	Internal Resistance	≤10 mΩ
	Cycle Life	>3500 cycles @1C 70%DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.5C
	Efficiency of Discharge	96-99% @1C
Standard Charge	Charge Voltage	29.2±0.2V
	Charge Mode	0.2C to 29.2V, then 29.2V charge current to 0.02C (CC/CV)
	Charger Current	50A
	Max. Charge Current	100A
	Charge Cut-off Voltage	29.2V±0.2V
Standard Discharge	Rated Discharge Current	50A
	Max Discharge Current	100A
	Max. Pulse Current	300A(<3s)
	Discharge Cut-off Voltage	20V
	Charge Temperature	0 °C to 45 °C (32Fto 113F) @60±25% Relative Humidity
	Discharge Temperature	-20 °C to 60 °C (-4F to 140F) @60±25% Relative Humidity
	Storage Temperature	0 °C to 40 °C (32Fto 104F) @60±25% Relative Humidity
	Water Dust Resistance	IP65
Mechanical	BMS	4S/4P
	Communication function	CAN BUS/NMEA 2000
	Plastic Case	ABS
	Dimensions (in./mm.)	483x170x240 mm
	Weight (lbs./kg.)	19.2kg(42.32lbs)
	Terminal	M8

