Lithium Iron Phosphate (LiFePO4) Battery

MBL25-50

25.6V50AH 1280Wh

Features of LiFePO4 Battery

Longer Cycle Life

LiFePO4 batteries have a cycle live five times higher than that of SLA batteries

High Power & Light weight

LiFePO4 batteries have twice the power of SLA batteries, while half the weight, helpful for transport and installation

Intelligent management control

Intelligent BMS system covered by LFP batteries to ensure that batteries work on safety and perfect condition

Lower Self-discharge rate

Lower Self-discharge rate to guarantee LFP batteries be stored more longer than SLA batteries



Physical Dimension

Applications

- Caravan, RV, camping
- UPS (replacement of SLA batteries)
- Marine, golf cart
- Solar, wind system
- PV, solar light

Electrical Characteristics	Chemistry	LiFePO4
	Nominal Voltage	25.6V
	Nominal Capacity	50Ah (C5,25°C)
	Energy	1280Wh
	Internal Resistance	≤10 mΩ
	Cycle Life	>3500 cycles @1C 70%DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.5C
	Efficiency of Discharge	96-99% @1C
Standard Charge	Charge Voltage	29.2±0.2V
	Charge Mode	0.2C to 29.2V, then 29.2V charge current to 0.02C (CC/CV)
	Charger Current	25A
	Max. Charge Current	50A
	Charge Cut-off Voltage	29.2V±0.2V
Standard Discharge	Rated Discharge Current	25A
	Max Discharge Current	50A
	Max. Pulse Current	150A(<3s)
	Discharge Cut-off Voltage	20V
	Charge Temperature	0 °C to 45 °C (32Fto 113F) @60±25% Relative Humidity
	Discharge Temperature	-20 °C to 60 °C (-4F to 140F) @60±25% Relative Humidity
	Storage Temperature	0 °C to 40 °C (32Fto 104F) @60±25% Relative Humidity
	Water Dust Resistance	IP65
Mechanical	BMS	4S/4P
	Plastic Case	ABS
	Dimensions (in./mm.)	307x169x208 mm
	Weight (lbs./kg.)	9.8kg(21.6lbs)
	Terminal	M6

