

😵 Bluetooth



## LiFePO4 12,8V 40Ah Battery

Weight

Storage

Self-discharge rate

Storage Temperature & Humidity Range

Art. 112.500

This 12.8V 40Ah LiFePO4 battery is a maintenance free battery which is suitable for different type of applications like cyclic and storage and also has an extremely long lifespan (>3000 90% DoD). With the built-in APP functionality, suitable for both Android and IOS, the battery status can be viewed from your phone or tablet.

Cyclic

Solar / Storage

**Stationary** 

Marine

The electronics have been adapted in such a way that the battery can be connected in series or in parallel without any problems.

Normal specification	
12,8V (4S)	
40Ah	
≤40mΩ	

Standard Charge	
Battery operation temperature range @charging	0~45°C
Normal charge voltage	14.6±0.1V
Recommended float charge voltage (for Standby	13.8±0.1V
use)	
Allowed MAX charge current	40A@Battery initial Temp 25±5°C
Recommended charge current	≤20A
Standard discharge	
Battery operation temperature range	-20~60°C
@discharging	
Output Voltage Range	8.0~14.6V
Allowed discharge current	20A Standard discharge current
	50A Maximum discharge current
Pulse discharge current	150A withstand 3s
Discharge Cut-off voltage	8.0V
Mechanical Characteristics	
	Longth 106+2mm
	Length 196±2mm
Dimension	Width 165,5±2mm
	Height 170±2mm

Approx. 6.8Kg

**Residual capacity** 

**Reversible capacity** 

Short: within one month -20~35°C, 45~75%RH

Long term: above one month -10~30°C, 45~75%RH

≤3% per month; ≤15% per year

≤1.5%per month; ≤8% per year

	<u> </u>
۲	6

