



intAct AGM-Power - Marine & Leisure

Sealed AGM battery with grid plates | electrolyte fixed in fleece | filled and charged | absolutely maintenance-free

Art.No.

AGM90

Volt	12V
Capacity	85 Ah (c5), 95 Ah (c20), 110 Ah (c100)
CCR -18°C (EN)	-
Electrolyte	diluted sulphuric acid
Electrolyte density	1,28 +/- 0,01 Kg/l (25° C)
Size (LxWxH)	353 x 175 x 190 mm
Weight	26 kg
Pos. of Terminal	0
Terminal	1
Bodenleiste	B13



Usage




Maintenance-free all-round


Completely sealed maintenance-free and leak-proof, therefore well suited for the interior. Uncomplicated power supply for hobby and leisure-time pursuits and smaller solar applications. Our recommendation for those looking for an affordable sealed supply battery.

- » **300 charging cycles according to IEC 254-1.**
- » **Longer service life** than flooded lead-acid battery.
- » **Low self-discharge.**
- » **VRLA battery with gas recombination and safety valves,** where refilling is neither possible or necessary.
- » **Sealed AGM battery with grid plates.**
- » **Leak-proof.** Can also be installed at an angle, as the electrolyte is absorbed in glass fibre mats and the battery is tightly sealed.


Size




Pos. of Terminal 0



Terminal 1



Bodenleiste B13



As of 10.12.2025