



EPSOLAR TECHNOLOGY



COMPANY PROFILE

EPSOLAR TECHNOLOGY

Beijing Epsolar Technology Co., Ltd. was established in March 2007 with more than 30 million RMB registered capital. We are a new and high-tech enterprise which was specialized in power products researching, manufacturing and marketing.

We provide products including solar charge controllers, off-grid inverter, LED driver and special power units etc., as well as design and supply relevant solar application systems. The company has passed the ISO9001: 2008, and products have passed CGC-SOLAR ,CE ,ROSH, FCC and ETL certificate, as well as other domestic and international authoritative certification and a number of patents. The products have been extensively applied and highly appraised in a number of major projects at home and abroad. And sell in more than 120 foreign countries and regions.

In July 2014, we established Shenzhen branch as our production base. In August 2014, we were listed in NATIONAL EQUITIES EXCHANGE AND QUOTATIONS and launched into capital market successfully.

BRAND INTRODUCTION



EP means “Efficient Power”, SOLAR means “Solar photovoltaic”. The Brand “EPSOLAR” indicates our main products and industry. It applies to solar charge controller products.



EP means “Efficient Power”, EVER means “FOR EVER”. The Brand “EPEVER” indicates our firm determination to provide high quality power products, and excellent customer service. It applies to inverters and all the controllers launched since 2015.



OUR ADVANTAGE

RAPID DEVELOPMENT

Since 2007, we have sold two million controllers for off grid systems in more than 120 countries and are in the process of developing many new products.

DIVERSIFIED PRODUCTS

We have 20 series, more than 100 models of products which can meet customers' different requirements.

INNOVATIVE DESIGN

Our technical team has over 20 years professional R&D experience. And our innovation will keep the customer one step ahead for ever.

QUALITY COMPONENTS

All our products use industrial grade electronic components from global well-known companies.

QUALITY CONTROL

With ISO9001 and ISO14001 certification, we build-up strict quality control systems from incoming components to final products.

HIGH COST PERFORMANCE

We design and provide high quality products at reasonable price.



Efficient Power We Supply



ISO9001:2008 ISO14001:2004 CE RoHS FC  IEC62509 IEC62109



CONTENTS

Solar Charge Controller

MPPT controller

01	TRIRON series
02	Tracer series
05	eTracer series
07	iTracer series

PWM controller

09	ViewStar series
12	LandStar series

Solar Charge Controller & LED Driver

22	Tracer-EPLI series
23	Tracer-LPLI series
24	Tracer-BPL series
25	Tracer-BP series
26	LS-LPLIseries
27	LS-LPLIseries
28	LS-BPL series
29	LS-GPLI series

LED Driver

30	DCCP series
----	-------------

Inverter Charger

31	Upower series
----	---------------

Pure Sine Wave Inverter

32	SHI series
33	STI series

Portable DC system

34	EPE series
----	------------

NEW



TRIRON series MPPT solar charge controller

10A,20A,30A,40A 12/24V auto work

TRIRON series modular design base on MPPT solar charge controller. The modularized controller is composed of MPPT solar controller and different display modules (LED, LCD) or interface modules (Relay, USB and RS485). The controller can recognize and upload the modules driver automatically. Customers can choose the corresponding module according to actual application. Only replace the module and power on the controller, it will be working. It can be widely used in communication station, household system and field monitoring and other fields.

Features:

- Recognize and upload the modules driver automatically
- Modular design is convenient maintenance and upgrade
- LCD, LED, Relay, USB or RS485 modules optional
- Advanced MPPT technology, tracking efficiency up to 99.5%
- Peak conversion efficiency of 98%
- Accurately recognizing and tracking of multiple power points
- Multiple load control modes
- Support 4 charging options: Sealed, Gel, Flooded and User
- RS485 port with industrial standard MODBUS open architecture
- Real-time energy statistics
- Relay design realize the perfect combination of inverter and controller

Application



Model	TRIRON1206N	TRIRON2206N	TRIRON2210N	TRIRON3210N	TRIRON4210N
Nominal system voltage	12/24V auto work				
Rated charge current	10A	20A	20A	30A	40A
Rated discharge current	10A	20A	20A	30A	40A
MPP voltage range	(Vbat+2V)~36V		(Vbat+2V)~72V		
Max. PV open circuit voltage	60V(at min operating environment temp.) 46V(at 25℃ environment temp)		100V at minimum operating environment temperature 92V at 25℃ environment temperature		
Max. PV input power	12V 130W	12V 260W		12V 390W	12V 520W
	24V 260W	24V 520W		24V 780W	24V 1040W
Self-consumption	≤20mA(12V), ≤16mA(24V)				
Temp. compensation	-3mV/℃/2V				
Grounding	Common positive				
Overall dimension	180.8x135x47.3 mm	216x150x56.7mm		238.3x158x62.7 mm	256.8x183x66.7 mm
Net weight	0.6kg	0.9kg		1.2kg	1.6kg
Enclosure	IP30				
Working temperature	-25℃ ~ +45℃				
Relative humidity	≤95% (N.C.)				



Tracer A series MPPT Solar charge controller

10A,20A,30A,40A 12/24V auto work

Tracer A series adopts advanced MPPT technology. It can fast and accurately MPP of photovoltaic array in any situation and obtain the maximum solar energy at any time, which remarkably improves energy efficiency. With Modbus communication protocol interface, it is convenient for user to expand applications and meet monitoring requirements in various fields like telecommunication base station, household system, lighting system etc.

Features:

- Advanced MPPT technology
- High tracking efficiency no less than 99.5%
- Peak conversion efficiency of 98%
- Ultra-fast tracking speed
- Accurately recognizing and tracking MPP of multiple wave crest
- Automatic PV power limit function
- Multi-function LCD displays system information intuitively
- User programmable for battery types, load control etc.
- 3-Stage charge with PWM output
- Common positive grounding design
- RS485 port with industrial standard MODBUS open architecture
- Fully programmable function via remote meter, PC software and Mobile APP.

Application



CE RoHS IEC62109

Electrical parameters	Tracer1210A	Tracer2210A	Tracer3210A	Tracer4210A
Nominal system voltage	12/24V auto work			
Rated battery current	10A	20A	30A	40A
Rated load current	10A	20A	30A	40A
MPP voltage range	(Vbat+2V)~72V			
Max. PV open circuit voltage	100V at minimum operating environment temperature 92V at 25°C environment temperature			
Max. PV input power	12V 130W	12V 260W	12V 390W	12V 520W
	24V 260W	24V 520W	24V 780W	24V 1040W
Self-consumption	≤20mA(12V), ≤16mA(24V)			
Temp. compensation	-3mV/°C/2V			
Grounding	Common positive			
Overall dimension	172x139x44mm	220x154x52mm	228x164x55mm	252x180x63mm
Net weight	0.6kg	1.1kg	1.2kg	1.9kg
Enclosure	IP30			
Working temperature	-25°C ~ +45°C			
Relative humidity	≤95% (N.C.)			



Tracer BN series MPPT solar charge controller

10A,20A,30A,40A 12/24V auto work

Tracer-BN Series is a flagship member among all tracer MPPT controllers. We design with very long lifespan industrial materials and die-cast aluminum housing cooling system, to improve the controller's performance and life.

Application



Features:

- Peak conversion efficiency of 98%
- High tracking efficiency $\geq 99.5\%$
- Die-cast aluminum design and nature cooling
- Diversified load control to meet different requirements
- Battery type selection: Sealed, Gel, Flooded and User(programmable)
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Field upgradable firmware



IEC62109

CE RoHS

Model	Tracer1215BN	Tracer2215BN	Tracer3215BN	Tracer4215BN
Nominal system voltage	12/24V auto work			
Rated battery current	10A	20A	30A	40A
Rated load current	10A	20A	20A	20A
Max. PV open circuit voltage	150V at minimum operating environment temperature 138V at 25°C environment temperature			
MPP voltage range	(Vbat+2V)~108V			
Battery input voltage range	8~32V			
Max. PV input power	130W (12V)	260W (12V)	390W (12V)	520W (12V)
	260W (24V)	520W (24V)	780W (24V)	1040W (24V)
Self-consumption	$\leq 50\text{mA}(12\text{V})$ $\leq 27\text{mA}(24\text{V})$			
Grounding	Common negative			
Temp. compensation	$-3\text{mV}/^{\circ}\text{C}/2\text{V}$			
Communication port	RS485 / RJ45 interface			
Overall dimension	196x118x36mm	217x143x56mm	281x160x60mm	303x183x64mm
Net weight	0.9kg	1.5kg	2.3kg	2.9kg
Enclosure	IP30			
Working temperature	$-25^{\circ}\text{C} \sim +55^{\circ}\text{C}$			
Relative humidity	$\leq 95\%$ (N.C.)			



Tracer CN series MPPT Solar charge controller

20A,30A 12/24V auto work

Tracer CN series adopts common negative design and advanced MPPT control algorithm, and introduces original dry contact design to achieve the switch of external equipment. The integration design not only replaces traditional electrical design using external relay, what is more can achieve multiple control modes and working modes, it can be widely used in household system, field monitoring and communication station etc.

Application



Features:

- Dry contact design, achieve the switch of external equipment
- Multiple dry contact control mode, local, remote and cross- network
- Multiple dry contact working modes: manual control, light ON/OFF, light on+timer and time control
- High tracking efficiency no less than 99.5%
- Peak conversion efficiency of 98%
- Accurately recognizing and tracking of multiple power point
- Automatic PV power limit function
- Real-time energy statistics function
- RS485 port with industrial standard MODBUS open architecture
- Fully programmable function via PC software or remote meter
- Support software upgrade

CE RoHS

Model	Tracer2210CN	Tracer3210CN
Nominal system voltage	12/24VDC auto work	
Rated charge current	20A	30A
Battery input voltage range	9V~32V	
Max. PV open circuit voltage	100V(at minimum operating environment temperature) 92V(at 25℃ environment temperature)	
MPP voltage range	(Vbat+2V)~72V	
Max. PV input power	260W(12V); 520W(24V)	390W(12V); 780W(24V)
Self-consumption	≤20mA(12V); ≤23mA(24V)	
Grounding	Common negative	
Temperature compensation coefficient	-3mV/ °C/2V	
Overall dimension	173x150x79.9mm	173x163x86mm
Net weight	1.21kg	1.46kg
Enclosure	IP20	
Working environment temperature	-35 °C ~+55 °C	
Relative humidity	≤95% (N.C.)	



eTracer BND series MPPT solar charge controller

45A,60A 12/24/36/48V auto work

eTracer is an intelligent, efficient, high-speed solar charge controller with advanced Maximum Power Point Tracking (MPPT) algorithm, which can harvest the maximum power from the solar array to charge battery. It can be applied in the off-grid PV systems up to 3KW, and increase the efficiency up to 30% .

Application



Features:

- High tracking efficiency $\geq 99.5\%$
- Peak conversion efficiency of 98% and full load efficiency of 97%
- Accurately tracking and recognizing MPP among multiple wave crest
- Battery type selection: Sealed, Gel, Flooded and User(programmable)
- Energy statistics recording
- Built-in running data and event logging
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Field upgradable firmware

IEC62109

CE RoHS

Model	ET4415BND	ET6415BND	ET6420BND
Nominal system voltage	12/24/36/48V auto work		
Rated Battery current	45A	60A	
Max. PV open circuit voltage	150V at minimum operating environment temperature 138V at 25℃ environment temperature		190V at minimum operating environment temperature 180V at 25℃ environment temperature
Battery input voltage range	8V~68V		
MPP voltage range	(Vbat+2V)~108V		
Max. PV input power	600W (12V)	800W (12V)	
	1200W (24V)	1600W (24V)	
	1800W (36V)	2400W (36V)	
	2400W (48V)	3200W (48V)	
Self-consumption	1.4~2.2W		
Grounding	Common negative		
Temp. compensation	-3mV/℃/2V		
Overall dimension	398.6x208x107mm	449x208x107mm	
Net weight	4.3kg	5.5kg	
Enclosure	IP20		
Working temperature	-25℃ ~ +55℃		
Relative humidity	≤95% (N.C.)		



eTracer AD series MPPT solar charge controller

45A,60A 12/24/36/48V auto work

eTracer is an intelligent, efficient, high-speed solar charge controller with advanced Maximum Power Point Tracking (MPPT) algorithm, which can harvest the maximum power from the solar array to charge battery. It can be applied in the off-grid PV systems up to 3KW, and increase the efficiency up to 30% .

Application



Features:

- High tracking efficiency $\geq 99.5\%$
- Peak conversion efficiency of 98% and full load efficiency of 97%
- Accurately tracking and recognizing MPP among multiple wave crest
- Battery type selection: Sealed, Gel, Flooded and User(programmable)
- Energy statistics recording
- Built-in running data and event logging
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Field upgradable firmware

CE RoHS

Model	ET4415AD	ET6415AD
Nominal system voltage	12/24/36/48V auto work	
Rated Battery current	45A	60A
Max. PV open circuit voltage	150V at minimum operating environment temperature 138V at 25°C environment temperature	
MPP voltage range	(Vbat+2V)~108V	
Battery input voltage range	8V~68V	
Max. PV input power	600W (12V)	800W (12V)
	1200W (24V)	1600W (24V)
	1800W (36V)	2400W (36V)
	2400W (48V)	3200W (48V)
Self-consumption	1.4~2.2W	
Grounding	Common positive	
Temp. compensation	-3mV/°C/2V	
Overall dimension	398.6x208x107mm	449x208x107mm
Net weight	4.3kg	5.5kg
Enclosure	IP20	
Working temperature	-25°C ~ +55°C	
Relative humidity	≤95% (N.C.)	



iTracer ND series MPPT controller with load control

45A,60A 12/24/36/48V auto work

iTracer is an intelligent, efficient, high-speed solar charge controller with advanced Maximum Power Point Tracking (MPPT) algorithm, which can harvest the maximum power from the solar array to charge battery. It can be applied in the off-grid PV systems up to 3KW, and increase the efficiency up to 30% .

Application



Features:

- High tracking efficiency $\geq 99.5\%$
- Peak conversion efficiency of 98% and full load efficiency of 97%
- Accurately tracking and recognizing MPP among multiple wave crest
- Battery type selection: Sealed, Gel, Flooded and User(programmable)
- Multiple load control modes
- Built-in running data and event logging
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Field upgradable firmware

CE RoHS  IEC62109

Model	IT4415ND	IT6415ND
Nominal system voltage	12/24 /36/48V auto work	
Rated battery current	45A	60A
Rated load current	45A	60A
Max. PV open circuit voltage	150V at minimum operating environment temperature 138V at 25°C environment temperature	
Battery input voltage range	8~68V	
MPP voltage range	(Vbat+2V)~108V	
Max. PV input power	600W (12V)	800W (12V)
	1200W (24V)	1600W (24V)
	1800W (36V)	2400W (36V)
	2400W (48V)	3200W (48V)
Self-consumption	1.4~2.2W	
Grounding	Common negative	
Temp. compensation	-3mV/°C/2V	
Overall dimension	382x231x107mm	440x231x110mm
Net weight	4.6kg	5.9kg
Enclosure	IP20	
Working temperature	-25°C ~ +45°C	
Relative humidity	≤95% (N.C.)	



iTracer AD series MPPT controller with load control

45A,60A 12/24/36/48V auto work

iTracer is an intelligent, efficient, high-speed solar charge controller with advanced Maximum Power Point Tracking (MPPT) algorithm, which can harvest the maximum power from the solar array to charge battery. It can be applied in the off-grid PV systems up to 3KW, and increase the efficiency up to 30% .

Application



Features:

- High tracking efficiency $\geq 99.5\%$
- Peak conversion efficiency of 98% and full load efficiency of 97%
- Accurately tracking and recognizing MPP among multiple wave crest
- Battery type selection: Sealed, Gel, Flooded and User(programmable)
- Multiple load control modes
- Built-in running data and event logging
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Field upgradable firmware



CE RoHS

Model	IT4415AD	IT6415AD
Nominal system voltage	12/24 /36/48V auto work	
Rated battery current	45A	60A
Rated load current	45A	60A
Max. PV open circuit voltage	150V at minimum operating environment temperature 138V at 25°C environment temperature	
MPP voltage range	(Vbat+2V)~108V	
Battery input voltage range	8~68V	
Max. PV input power	600W (12V)	800W (12V)
	1200W (24V)	1600W (24V)
	1800W (36V)	2400W (36V)
	2400W (48V)	3200W (48V)
Self-consumption	1.4~2.2W	
Grounding	Common positive	
Temp. compensation	-3mV/°C/2V	
Overall dimension	382x231x107mm	440x231x110mm
Net weight	4.6kg	5.9kg
Enclosure	IP20	
Working temperature	-25°C ~ +45°C	
Relative humidity	≤95% (N.C.)	

VS-A series PWM solar charge controller

10A,20A,30A 12/24V auto work



VS-A series is common positive controller with LCD display, adopting the most advanced digital technique, high cost performance.

Application



Features:

- PWM charging
- Battery type selection: Sealed, Gel, Flooded
- Multi-function LCD displays system information intuitively
- Multiple load control modes
- Energy statistics function
- Optional RTS for accurate temperature compensation
- Extensive electronic protection

CE RoHS

Model	VS1024A	VS2024A	VS3024A
Nominal system voltage	12/24V auto work		
Rated battery current	10A	20A	30A
Rated load current	10A	20A	30A
Battery input voltage range	9~32V		
Max. PV open circuit voltage	50V		
Self-consumption	≤8.1mA(12V);≤6.5mA(24V)		
Grounding	Common positive		
Temp. compensation	-3mV/°C/2V		
Overall dimension	132x84.6 x39.7mm	149x94.1x46.1mm	177.5x106.6x46.2mm
Terminals	4mm ²	16mm ²	16mm ²
Net weight	0.18kg	0.26kg	0.33kg
Enclosure	IP30		
Working environment temperature	-25℃~+45℃		
Relative humidity	≤95% (N.C.)		

VS-AU series PWM solar charge controller

10A,20A,30A,45A,60A 12/24/36/48V auto work



The VS-AU controller is a PWM charge controller with built in LCD display that adopts the most advanced digital technique. The multiple load control modes enable it can be widely used on solar home system, traffic signal, solar street light, solar garden lamp, etc.

Application



Features:

- 3-Stage intelligent PWM charging: Bulk, Boost/Equalize, Float
- Support 3 charging options: Sealed, Gel, and Flooded
- LCD display design, dynamically displaying device's operating data and working condition
- Double USB design, the power supply charge for electronic equipment
- With humanized button settings, operation will be more comfortable and convenient
- Multiple load control modes
- Energy statistics function
- Extensive Electronic protection

CE RoHS

Model	VS1024AU	VS2024AU	VS3024AU	VS4524AU	VS6024AU
			VS3048AU	VS4548AU	VS6048AU
Nominal system voltage	VS**24AU 12/24V auto work		VS**48AU 12/24/36/48V auto work		
Battery input voltage range	VS**24AU 9~32V		VS**48AU 9V~64V		
Rated charge/discharge current*	10A	20A	30A	45A	60A
Max. PV open circuit voltage	VS**24AU 50V VS**48AU 96V				
Grounding	Common positive				
USB output	5VDC/2.4A(Total)				
Overall dimension	142x85x41.5 mm	160x94.9x49.3 mm	181x100.9x59.8 mm	194x118.4x63.8 mm	214x128.7x72.2 mm
Terminals	12AWG(4mm ²)	8AWG(10mm ²)	6AWG(16mm ²)	6AWG(16mm ²)	3AWG(25mm ²)
Net weight	0.22kg	0.35kg	0.55kg	0.76kg	1.02kg
			0.58kg	0.88kg	1.04kg
Enclosure	IP30				
Working environment temperature	-25℃~+55℃ (Product can work continuously at full load)				
Relative humidity	≤95% (N.C.)				



VS-BN series PWM solar charge controller

10A,20A,30A,45A,60A 12/24V auto work
20A,30A,45A,60A 12/24/36/48V auto work

This VS-BN series is common negative controller, with LCD display, working data programmable, It has communication function via RS485 port to PC monitoring software, realizing real-time monitoring and battery management parameter setting.

Application



Features:

- Battery type selection: Sealed, Gel, Flooded, and User (programmable)
- Intelligent lighting and timer control for solar lighting system
- Full control parameters setting and modification, diversified load control mode
- Humanized design of browser interface
- Adopt graphics dot-matrix LCD screen and 4 buttons for integrated menu displaying and operation
- Real-time energy statistics
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Support firmware upgrade

CE RoHS

Model	VS1024BN	VS2024BN VS2048BN	VS3024BN VS3048BN	VS4524BN VS4548BN	VS6024BN VS6048BN
Rated battery current	10A	20A	30A	45A	60A
Rated load current	10A	20A	30A	45A	60A
Nominal system voltage	VS**24BN 12/24V auto work, VS**48BN 12/24/36/48V auto work				
Max. battery voltage	12/24V 34V, 12/24/36/48V 64V				
Self-consumption	≤15mA(12V); ≤10mA(24V); ≤9mA(36V); ≤8mA(48V)				
Grounding	Common negative				
Temp. compensation	-3mV/°C/2V				
Overall dimension (mm)	162x85x40	162x100x50	200x103x58	201x109x59	205x129x67
		200x103x58	201x109x59	205x119x67	205x174x64
Net weight	0.4kg	0.4kg	0.7kg	0.9kg	1.3kg
		0.7kg	0.9kg	1.2kg	1.5kg
Enclosure	IP30				
Working temperature	-35°C ~ +55°C				
Relative humidity	≤95% (N.C.)				

LandStar E series PWM solar charge controller

5A,10A,20A 12V/24V



LS-E series is reliable, stable, and economical solar charge controller, easy for operation.

Application



Features:

- PWM charging
- Use MOSFET as electronic switch
- Intuitive LED indicators showing battery voltage status
- Battery type selection: Gel, Sealed, and Flooded
- Manual control the output of the load
- Temperature compensation
- Industrial grade design

CE RoHS

Model	LS0512E	LS1012E	LS1024E	LS2024E
Rated battery current	5A	10A	10A	20A
Rated load current	5A	10A	10A	20A
Nominal system voltage	12V	12V	12/24V auto work	12/24V auto work
Battery input voltage range	8~16V	8~16V	8~32V	8~32V
Self-consumption	≤6mA			
Grounding	Common positive			
Temp. compensation	-5mV/°C/2V			
Overall dimension	92.8x65x20.2mm	101.2x67x21.8mm	101.2x67x21.8mm	128x85.6x34.8mm
Net weight	74g	82.5g	82g	151.6g
Enclosure	IP30			
Working temperature	-35°C ~ +55°C			
Relative humidity	≤95% (N.C.)			

LandStar EU series PWM solar charge controller

5A,10A,20A,30A 12V/24V



LS-EU series is reliable, stable, and economical solar charge controller, easy for operation.

USB output can charge mobile phone, DC fans, and other DC electronic device.

Application



Features:

- With USB port
- PWM charging
- Use MOSFET as electronic switch
- Intuitive LED indicators showing battery voltage status
- Battery type selection: Gel, Sealed, and Flooded
- Manual control the output of the load
- Temperature compensation
- Industrial grade design

CE RoHS

Model	LS0512EU	LS1012EU	LS1024EU	LS2024EU	LS3024EU
Rated battery current	5A	10A	10A	20A	30A
Rated load current	5A	10A	10A	20A	30A
Nominal system voltage	12V	12V	12/24V auto work	12/24V auto work	12/24V auto work
Battery input voltage range	8~16V	8~16V	8~32V	8~32V	8~32V
Self-consumption	12V≤5mA; 24V≤7mA				
Grounding	Common positive				
Temp. compensation	-5mV/°C/2V				
USB output	5VDC/1.2A				5VDC/2A
Overall dimension (mm)	109.7x65.5x20.8	120.3x67x21.8	120.3x67x21.8	148x85.6x34.8	148x106.8x43.7
Net weight	95g	103g	102g	179.6g	290g
Enclosure	IP20				
Working temperature	-35°C ~ +55°C				
Relative humidity	≤95% (N.C.)				

LandStar B series PWM solar charge controller

10A,20A,30A 12/24V auto work



Landstar B series controller with high reliability, accuracy of sampling and full electronic protection. Programmable via remote meter MT50 ,PC software and APP.

Application



Features:

- PWM charging
- Three LEDs shows PV charging, battery and load status
- Optional RTS for accurate temperature compensation
- RS485 port with industrial standard MODBUS open architecture
- Multiple load working modes: Manual Control, Light ON/OFF, Light On+Timer and Time Control
- Battery type selection: Sealed, Gel, Flooded and User(programmable)
- Battery temperature compensation
- Real-time energy statistics
- RS485 port with industrial standard MODBUS open architecture
- Real-time data monitoring and parameters setting with MT50, APP or PC software
- Support firmware upgrade

CE RoHS IEC62109

Model	LS1024B	LS2024B	LS3024B
Rated battery current	10A	20A	30A
Rated load current	10A	20A	30A
Nominal system voltage	12/24V auto work		
Battery input voltage range	8~32V		
Self-consumption	≤8.4 mA/12V; ≤7.8mA/24V		
Grounding	Common positive		
Temp. compensation	-3mV/°C/2V		
Overall dimension	138.6x69.3x37mm	159.6x81.4x47.8mm	200.6x 101.3x57mm
Net weight	0.13kg	0.3kg	0.5kg
Enclosure	IP30		
Working temperature	-35℃ ~ +50℃		
Relative humidity	≤95% (N.C.)		

LS-BP series PWM solar charge controller

10A,20A 12/24V auto work



New LandStar series is Epsolar's new generation programmable solar charge controller. Fully encapsulated PCB, IP67 design, aluminum case ensures the controller can work in extremely terrible, and increase system operation, reliability and efficiency.

Application



Features:

- High efficient Series PWM charging, increase the battery lifetime and improve the solar system performance.
- Use MOSFET as electronic switch, without any mechanical switch.
- Multiple load control modes, increase the flexibility of the load output
- Gel, Sealed, Flooded and user-defined battery type option.
- New SOC method of calculating accurately displays the available battery capacity.
- The control function and the switch condition of the load can be modified by communication connection.
- Use of standard Modbus communication protocol for TTL-232 bus connections
- Support firmware upgrade
- Fully encapsulated PCB, IP67 protection
- Aluminum housing

CE RoHS

Model	LS1024BP	LS2024BP
Rated battery current	10A	20A
Rated load current	10A	20A
Nominal system voltage	12/24V auto work	
Max. battery voltage	32V	
Self-consumption	≤8.4 mA/12V; ≤7.8mA/24V	
Grounding	Common positive	
Temp. compensation	-3mV/°C/2V	
Overall dimension	108.5x64.5x25.6mm	139x 76.5x28mm
Net weight	0.4kg	0.6kg
Enclosure	IP67	
Working temperature	-35°C ~ +55°C	



LS-BPD series PWM Solar Charge Controller

10A,20A 12/24V auto work

LS-BPD series is a waterproof charge controller with automatic lighting control function, ideal for extreme environments with corrosion, dust, moisture etc.

Features:

- PWM charging
- Battery type selection : Gel, Sealed and Flooded
- LVD programmable (10.6V - 12V for 12V system)
- Temperature compensation function
- Automatic lighting control
- LED indicators for PV and battery status
- Diversified load control modes option
- Intelligent dual timer function with 1 ~ 14 hours option
- Fully encapsulated PCB, IP67 protection
- Aluminum housing for better cooling
- Application: solar lighting system, solar monitoring system, solar home system

CE RoHS

Model	LS1024BPD	LS2024BPD
Nominal system voltage	12/24V DC auto work	12/24V DC auto work
Rated charge current	10A	20A
Rated discharge current	10A	20A
Max. PV open circuit voltage	50V	
Battery type	Sealed (Default) / Gel / Flooded	
Self-consumption	9.4mA/12V;12.2mA/24V	
Temp. compensation coefficient	-3mV/°C/2V	
Grounding	Common positive	
Overall dimension	108.5x64x25.6mm	108.5x83x25.6mm
Power cable	14AWG(2.5mm ²)	12AWG(4mm ²)
Net weight	0.33kg	0.41kg
Enclosure	IP67	
Working environment temperature	-35°C ~ +55°C	



LandStar series PWM solar charge controller

5A,10A,20A 12V/24V
Light and timer control

LandStar series solar charge controller that adopts the most advanced digital technique and operates fully automatically. Light and timer control (Single timer and dual timer optional) Ideal for public lighting area, such as street light, path way, garden lights, parking area, bus station etc.

Application



Features:

- High efficient Series PWM charging
- Use MOSFET as electronic switch
- Widely used, automatically recognize day/night
- Digital LED menu with simple setting and easy using
- Intelligent timer function with 1-15 hours option
- Gel, Sealed and Flooded battery type option
- Temperature compensation

CE RoHS

Model	LS0512R	LS1024R	LS2024R
Rated battery current	5A	10A	20A
Rated load current	5A	10A	20A
Nominal system voltage	12V	12/24V auto work	
Max. battery voltage	16V	32V	
Self-consumption	≤6mA		
Grounding	Common positive		
Temp. compensation	-5mV/°C/2V		
Overall dimension	97x66x25mm	140x65x34mm	144x 75x45mm
Net weight	0.05kg	0.15kg	0.25kg
Enclosure	IP30		
Working temperature	-35℃ ~ +55℃		
Relative humidity	≤95% (N.C.)		



LS-EPD series PWM solar charge controller

10A,20A 12/24V auto work

Light and timer control, Waterproof , IP67

LS-EPD series solar charge controller is an affordable waterproof charge controller with automatic lighting control function, ideal for extreme environments with corrosion, dust, moisture etc.

Application



Features:

- PWM charging
- For sealed battery charging
- Temperature compensation function
- Automatic lighting control
- LED indicators for PV and battery status
- Digital tube menu, only one key solve all settings simply
- Intelligent timer function with 1~13 hours option
- Fully encapsulated PCB, IP67 protection

CE RoHS

Model	LS1012EPD	LS1024EPD	LS2024EPD
Rated battery current	10A	10A	20A
Rated load current	10A	10A	20A
Nominal system voltage	12V	12/24V auto work	
Max. PV input voltage	30V	50V	50V
Self-consumption	12V: ≤4.58mA; 24V: ≤6.01mA		
Grounding	Common positive		
Temp. compensation	-5mV/°C/2V		
Overall dimension	108.5×75×25.6mm		
Net weight	408g	410g	435g
Enclosure	IP67		
Working temperature	-35°C ~ +55°C		



LandStar series PWM solar charge controller

10A,20A 12/24V auto work
Surfacing mounting, Manual ON/OFF

All the terminals backwards. Ideal for surfacing mounting solar system, such as solar home system, portable solar system.

Application



Features:

- Surfacing mounting
- High efficient Series PWM charging
- Gel, Sealed and Flooded battery type option
- Select battery type by jumper, simple and practical
- LED indicator shows battery level, direct and convenient
- Use MOSFET as electronic switch
- Temperature compensation
- Electronic protection: over charging, over discharging, overload, short circuit , and overheating
- Reverse protection: any combination of solar module and battery

CE RoHS

Model	LS1024S	LS2024S
Rated battery current	10A	20A
Rated load current	10A	20A
Nominal system voltage	12/24V auto work	
Max. battery voltage	32V	
Self-consumption	≤6mA	
Grounding	Common positive	
Temp. compensation	-5mV/°C/2V	
Overall dimension	120x68x40mm	128x 87x48mm
Net weight	0.15kg	0.25kg
Enclosure	IP30	
Working temperature	-35°C ~ +55°C	
Relative humidity	≤95% (N.C.)	



EP series PWM solar charge controller

10A,12/24V auto work

EP series is economic controller for solar home system and other small solar systems. All the electronic components are industrial grade without any mechanical switch. The electronic protections ensure the reliability of system.

Application



Features:

- Intelligent System Optimum Control
- 12/24V auto work
- High efficient Series PWM charging with temperature compensation
- Use MOSFET as electronic switch, without any mechanical switch
- Load and battery status indicators
- Electronic protection: over charging, over discharging, overload, and short circuit

CE RoHS

Model	EPRC10-EC
Rated battery current	10A
Rated load current	10A
Nominal system voltage	12/24V auto work
Self-consumption	≤6 mA
Grounding	Common positive
Temp. compensation	-5mV/°C/2V
Overall dimension	140 x89 x27mm
Net weight	0.23kg
Enclosure	IP30
Working temperature	-35°C ~ +55°C
Relative humidity	≤95% (N.C.)

EIPDB-COM series

Dual battery solar controller

10A, 20A 12/24V auto work



EIPDB-COM is dual battery charge controller for caravans, RVs, boats and golf cart etc. Two batteries charging eliminate the extra cost of two separate solar charging systems.

Application



Features:

- Two battery charging eliminates the extra cost of two separate solar charging system
- Intelligent System Optimum Control
- 12/24V auto work
- Battery type selection
- Charging frequency optional
- High efficient Series PWM charging
- Local external temperature compensation
- Remote temperature sensor optional
- Use MOSFET as electronic switch, without any mechanical switch
- Remote meter MT-1 optional
- Electronic protection: over charging, short circuit, battery reverse polarity protection

CE RoHS

Model	EIPDB-COM
Rated battery current	10A, 20A
Rated load current	12/24V auto work
Nominal system voltage	≤6 mA
Self-consumption	Common positive
Grounding	-5mV/°C/2V
Temp. compensation	153 x76 x37mm
Overall dimension	0.24kg
Net weight	IP30
Enclosure	-35°C ~ +55°C
Relative humidity	≤95% (N.C.)

MPPT



Tracer-EPLI series MPPT Solar Charge Controller & LED Driver

10A, 15A, 20A 12V/24V

TRACER-EPLI series combines solar charge controller and LED driver into one unit. It is ideal for solar LED Lighting requiring dimmer function. The control parameter can be programmed by Mobile APP and SPP-02 via infrared(IR) communication

Features:

- High tracking efficiency $\geq 99.5\%$
- Peak conversion efficiency of 98%
- Ultra-fast tracking speed and guaranteed tracking efficiency
- Accurately recognizing and tracking MPP of multiple wave crest
- Digital precision constant current control
- Maximum output efficiency of 96%
- Output current adjustable
- Flexible dimming function(0-100%)
- Real-time energy statistics function
- Easy to check system working status via Mobile APP

CE RoHS

Model	Tracer1305EPLI	Tracer2606EPLI	Tracer3906EPLI	Tracer5206EPLI
		Tracer2610EPLI	Tracer3910EPLI	Tracer5210EPLI
Nominal system voltage	12V	12/24V auto work		
Rated charge current	10A	10A	15A	20A
Rated charge power	130W	130W/12V 260W/24V	195W/12V 390W/24V	260W/12V 520W/24V
Max. PV open voltage	50V(Min.Temp.) 45V(25℃)	Tracer****06EPLI:60V(at Min. operating environment temp.) Tracer**10EPLI:46V (at 25℃ environment temp.)		
MPP Voltage range	Tracer**05/06EPLI: (Vbat +2V)~36V, Tracer**10EPLI:(Vbat +2V)~72V			
Max. output current	3.3A	3.3A	4.5A	6.6A
Max. output power	100W	100W	130W	200W
Maximum output efficiency	96%			
Self-consumption	≤15mA(12V);≤22mA(24V)			
Temp. compensation	-3mV/℃/2V			
Communication	IR communication			
Overall dimension	124x89 x30mm		150x93.5x32.7mm	153.3x105x52.1mm
Net weight	0.51kg	0.52kg	1.19kg	1.19kg
Enclosure	IP68(1.5m,72h)			
Working environment temperature	-40℃～+60℃			

MPPT



Tracer-LPLI series

Lithium Battery Solar Charge Controller with built-in LED Driver

10A, 20A 12/24V auto work

The Tracer LPLI series lithium battery MPPT solar charge controller combines solar charge controller and LED constant current driver into one unit which is ideal for solar LED Lighting, especially when dimmer function is needed. The advanced Maximum Power Point Tracking charging methods enables the system charging and discharging management to obtain the most radical optimization. Increase the system flexibility, yet lower down the system cost.

Features:

- High tracking efficiency no less than 99.5%-
- Peak conversion efficiency of 98%
- Lithium battery self-activating function
- Lithium battery low temperature protection function
- Battery type selection: LiFePO4, Li-NiCoMn and User (programmable)
- Maximum output efficiency of 96%
- Flexible dimming function (0~100%)

CE RoHS

Model	Tracer1305LPLI	Tracer2606LPLI	Tracer3906LPLI	Tracer5206LPLI
		Tracer2610LPLI	Tracer3910LPLI	Tracer5210LPLI
Nominal system voltage	12V	12/24V auto work		
Rated charge current	10A	10A	15A	20A
Rated charge power	130W	130W/12V 260W/24V	195W/12V 390W/24V	260W/12V 520W/24V
Max. PV open voltage	50V(Min.Temp.) 45V(25℃)	Tracer****06EPLI:60V(at Min. operating environment temp.) Tracer**10EPLI:46V (at 25℃ environment temp.)		
MPP Voltage range	Tracer**05/06EPLI: (Vbat +2V)~36V, Tracer**10EPLI:(Vbat +2V)~72V			
Max. output current	3.3A	3.3A	4.5A	6.6A
Max. output power	100W	100W	130W	200W
Maximum output efficiency	96%			
Self-consumption	≤15mA(12V);≤22mA(24V)			
Temp. compensation	-3mV/℃/2V			
Communication	IR communication			
Overall dimension	124x89 x30mm		150x93.5x32.7mm	153.3x105x52.1mm
Net weight	0.51kg	0.52kg	1.19kg	1.19kg
Enclosure	IP68(1.5m,72h)			
Working environment temperature	-40℃～+60℃			

MPPT



Tracer-BPLseries

MPPT Solar Charge Controller with built-in LED Driver

The Tracer-BPL series lithium battery MPPT solar charge controller combines solar charge controller and LED constant current driver into one unit which is ideal for solar LED Lighting, especially when dimmer function is needed. The advanced Maximum Power Point Tracking charging methods enables the system charging and discharging management to obtain the most radical optimization. Increase the system flexibility, yet lower down the system cost.

Features:

- Adopt high quality components of ST,IR and Infineon, make sure product using lifespan
- Wide working environment temperature(-40℃~60℃)
- Apply to lithium battery(LiFePO4/Li-NiCoMn)and battery(Sealed/Gel/Flooded)
- Lithium battery self-activating and low temperature protection function
- Advanced Maximum Power Point Tracking (MPPT) technology, with tracking efficiency no less than 99.5%
- Maximum output efficiency of 96%
- The RS485 connector can provide power supply (5VDC/150mA)
- IP67 waterproof degree

CE RoHS

Model	Tracer2606BPL	Tracer3906BPL	Tracer5206BPL
	Tracer2610BPL	Tracer3910BPL	Tracer5210BPL
Nominal system voltage	12/24VDC Auto (Lithium battery no rated voltage level)		
Rated charge current	10A	15A	20A
Rated charge power	130W/12V 260W/24V	195W/12V 390W/24V	260W/12V 520W/24V
Max. PV open circuit voltage	Tracer**06BPL: 60V at minimum operating environment temperature 46V at 25℃ environment temperature Tracer**10BPL: 95V at minimum operating environment temperature 92V at 25℃ environment temperature		
MPP Voltage range	Tracer**06BPL: (Battery voltage+2V)~36V Tracer**10BPL: (Battery voltage+2V)~72V		
Max. output current	3.3A	4.5A	6.6A
Max. output power	100W	130W	200W
Output voltage range	Tracer**06BPL: (Max. battery voltage+2V)~58V Tracer**10BPL: (Max. battery voltage+2V)~80V		
Maximum output efficiency	96%		
Self-consumption	≤15mA/12V;≤22mA/24V		
Communication	RS485		
Overall dimension	124×89×30mm	150×93.5×32.7mm	153.3×105×52.1mm
Net weight	0.54kg	0.73kg	1.18kg
Enclosure	IP67		
Working environment temperature	-40℃~+60℃		

MPPT



Tracer-BPseries

MPPT Solar Charge Controller with built-in LED Driver

The Tracer-BP series solar charge controller adopt the advanced Maximum Power Point Tracking charging methods, it enables the system charging and discharging management to obtain the most radical optimization. Increase the system flexibility, yet lower down the system cost. The controller support a variety of battery, for example sealed, gel, flooded and lithium battery. User can view and modify the working status and parameters. It can be widely used on solar home system, traffic signal, solar street light, solar garden lamp, etc.

Features:

- Advanced MPPT technology
- High tracking efficiency no less than 99%
- Maximum conversion efficiency of 98%
- Ultra-fast tracking speed and guaranteed tracking efficiency
- Accurately recognizing and tracking of multiple power points
- Apply to lithium battery(LiFePO4/Li-NiCoMn)and battery (Sealed/Gel/Flooded)
- Lithium battery self-activating and low temperature protection function
- Real-time energy statistics function
- PV power limitation function
- Aluminum housing for better cooling
- Monitoring and setting parameter via Mobile APP, PC Monitor setting software with RS485 communication interface.

CE RoHS

Model	Tracer2606BP	Tracer3906BP	Tracer5206BP
	Tracer2610BP	Tracer3910BP	Tracer5210BP
Nominal system voltage	12/24VDC Auto (Lithium battery no rated voltage level)		
Rated charge current	10A	15A	20A
Rated charge power	130W/12V 260W/24V	195W/12V 390W/24V	260W/12V 520W/24V
Max. PV open circuit voltage	Tracer**06BP: 60V at minimum operating environment temperature 46V at 25°C environment temperature Tracer**10BP: 100V at minimum operating environment temperature 92V at 25°C environment temperature		
MPP Voltage range	Tracer**06BP: (Battery voltage+2V)~36V Tracer**10BP: (Battery voltage+2V)~72V		
Self-consumption	≤13mA/12V;≤11.5mA/24V		
Overall dimension	124×89×30mm	150×93.5×32.7mm	153.3×105×52.1mm
Net weight	0.54kg	0.74kg	1.2kg
Enclosure	IP67		
Working environment temperature	-40℃~+60℃		

PWM



LS-EPLI series Solar Charge Controller & LED Driver

10A, 20A 12V/24V

LS-EPLI series combines solar charge controller and LED driver into one unit. It is ideal for solar LED Lighting requiring dimmer function. The control parameter can be programmed by Mobile APP and SPP-02 via infrared(IR) communication.

Features:

- Battery type selection: Sealed, Gel, Flooded and User(programmable).
- Maximum output efficiency of 96%
- Output current adjustable
- Flexible dimming function(0-100%)
- Digital precision constant current control
- Real-time energy statistics function
- Battery temperature compensation function
- Fully encapsulated PCB, IP68 protection
- Aluminum housing for better cooling
- Easy to check system working status via Mobile APP

CE RoHS

Model	LS101240EPLI	LS102460EPLI	LS2024100EPLI
Nominal system voltage	12V	12/24V	12/24V
Rated charge current	10A	10A	20A
Max. PV input voltage	30V	50V	50V
Rated output power	40W	30W/12V, 60W/24V	50W/12V, 100W/24V
Battery terminal voltage	9~16V	9~32V	9~32V
Rated output power	60W	100W	200W
Rated output current	2.6A	2.0A	3.3A
Self-consumption	12V:≤9.1mA; 24V:≤7.0mA		
Overall dimension	108.5x100.5x25.6mm	108.5x100.5x25.6mm	108.5x118x25.6mm
Net weight	0.23kg	0.23kg	0.28Kg
Enclosure	IP68		
Working temp.	-35℃~+55℃		

Lithium
battery



LS-LPLI series Solar Charge Controller & LED Driver

10A, 20A 12V/24V

The LS-LPLI series solar charge controller combines the solar charge controller and LED constant current driver into one unit which is ideal for solar LED Lighting, especially for the application for LED lamp which requires dimmer function. The advanced pulse width modulation charging methods enables the system charging and discharging management to obtain the most radical optimization. Make the system cost reduce, and increase the system flexibility.

Features:

- Apply to lithium battery
- Lithium battery self-activating function
- Lithium battery low temperature protection function
- Load reduce power automatically
- Battery type selection: LiFePO₄, Li-NiCoMn and User (programmable)
- Maximum output efficiency of 96%
- Output current adjustable
- Flexible dimming function (0~100%)
- Real-time energy statistics function
- Parameter setting via mobile APP(android only), RC-02 and SPP-02

CE RoHS

Model	LS101240LPLI	LS102460LPLI	LS2024100LPLI
Nominal system voltage	12V	12/24V auto work	
Battery input voltage range	9~16V	9~32V	
Max. PV open circuit voltage	30V	50V	50V
Rated charge current	10A	10A	20A
Max. output power	40W	30W/12V, 60W/24V	50W/12V, 100W/24V
Max. output current	2.6A	2.0A	3.3A
Max. output efficiency	96%		
Output voltage range	(Max. battery voltage+2V)~60V		
Load open circuit voltage	60V		
Self-consumption	≤18mA(12V); ≤23mA(24V)		
Battery Type	LiFePO4/ Li-NiCoMn /User		
Communication	IR communication		
Overall dimension	107x68x20mm	108.5x88x25.6mm	
Net weight	0.23kg	0.39kg	
Enclosure	IP68		
Working environment temperature	-35℃~+55℃		



LS-BPL series Solar Charge Controller & LED Driver

10A, 20A 12/24V auto work

LS-BPL series combines solar charge controller and LED driver into one unit. It is ideal for solar LED Lighting requiring dimmer function. The control parameter can be programmed by Mobile APP ,SPP-02 and PC software.

Features:

- Battery type selection: Sealed, Gel, Flooded and User(programmable).
- Flexible dimming function(0-100%)
- Battery temperature compensation
- Digital precision constant current control
- Maximum output efficiency of 96.7%
- Output current adjustable
- Parameter programmable via Mobile APP, PC software
- RS485 port with industrial standard MODBUS open architecture
- Aluminum housing for better cooling
- Fully encapsulated PCB, IP67 protection

CE RoHS

Model	LS102460BPL	LS2024100BPL
Nominal system voltage	12/24V auto work	
Battery input voltage range	9~32V	
Max. PV open circuit voltage	50V	
Rated charge current	10A	20A
Max. output power	30W/12V, 60W/24V	50W/12V, 100W/24V
Max. output current	2.0A	3.3A
Max. output efficiency	96.7%	
Output voltage range	(Max. battery voltage+2V)~60V	
Load open circuit voltage	60V	
Self-consumption	≤11mA(12V); ≤9mA(24V)	
Temp. compensation coefficient	-3mV/°C/2V	
Grounding	Common Positive	
Overall dimension	107x73x20mm	108.5x102x25.6mm
Net weight	0.28kg	0.46kg
Enclosure	IP67	
Working environment temperature	-35℃~+55℃	



LS-GPLI series PWM Solar Charge Controller with built-in LED Driver

10A, 20A 12/24V auto work

LS-GPLI series combines solar charge controller and LED constant current driver into one unit which is ideal for solar LED lighting, especially when dimmer function is needed. Full waterproof and IR communication design, it has the feature of high efficiency, high control accuracy and dimmer function. The product is dedicated in LED indoor and outdoor lighting application condition, such as road lighting, landscape lighting and billboard lighting etc.

Features:

- Maximum output efficiency of 96%
- Without any button, parameter setting via Mobile APP and RC-01 with IR function
- Flexible dimmer function, 0 ~ 100% can be adjusted
- Multiple load control modes, LED rated current and current percentage can be set.
- Load test function for detecting the system, the controller power on, the load is ON.
- Aluminum housing for better cooling
- Fully encapsulated PCB, IP68 protection (1.5 meters, 72h)
- Long lifespan design

CE RoHS

Model	LS102480GPLI	LS2024100GPLI
Nominal system voltage	12/24VDC auto work	
Rated charge current	10A	20A
Max. PV open circuit voltage	50V	50V
Max. output power	40W/12V;80W/24V	50W/12V;100W/24V
Max. output current	4A	5A
Max. output voltage	Min. Vbat-0.5V(12V) Min. Vbat -1V(24V)	
Maximum output efficiency	96%	
Self-consumption	≤16mA(12V);≤20mA(24V)	
Temp. compensation coefficient	-3mV/°C/2V	
Overall dimension	107x68x20mm	108.5x88x25.6 mm
Net weight	0.25kg	0.39kg
Enclosure	IP68 (1.5m,72h)	
Working environment temperature	-35°C~+55°C	



DCCP-DPRI series LED driver

DCCP-DPRI Series DC LED driver adopts the step-up voltage control, constant current driver design. The rated current range and working time is adjustable via infrared communication. The IP68 protection allows this series to fit both indoor and outdoor LED lightings, especially for solar LED lighting application.

Features:

- Maximum output efficiency of 95.7%
- Flexible dimming function (0-100%)
- Input surge suppression function
- Programmable via IR communication
- Wide working environment temperature ($-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$)
- Long lifespan design
- Fully encapsulated PCB, IP68 protection (1.5 meters, 72h)
- Aluminum housing for better cooling

CE RoHS

Model	DCCP6060DPRI	DCCP10060DPRI
Input voltage range	9V~33V	
Input surge voltage	3A/12V;6A/24V	6A/12V;12A/24V
Max. output current	2.0A	3.3A
Max. output power	30W/12V;60W/24V	50W/12V;100W/24V
Output voltage range	(Input voltage+2V)~60V	
Load open circuit voltage	60V	
Maximum output efficiency	95.7%	
Self-consumption	$\leq 10\text{mA}(12\text{V}) ; \leq 14\text{mA}(24\text{V})$	
Overall dimension	108.5x58x25.6mm	108.5x79x25.6mm
Net weight	0.25Kg	0.34Kg
Enclosure	IP68	
Working temp.	$-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$	

NEW



UPower series Inverter Charger

UPower series is a new type of hybrid Inverter charger which combines Solar energy & Utility electricity charging and AC output. It adopts the multi-core processor design and advanced control algorithm, with the feature of high response speed, high reliability and high industrial standards, etc. The inverter charger with LCD Display has four charging mode and two output mode. The extensive electronic protection ensures the system to work more safely, stably and durably.

Features:

- Adoption of advanced SPWM technology, pure sine wave output
- Digital voltage & current double closed-loop control
- Advanced MPPT technology, with efficiency no less than 99.5%.
- Support 4 charging mode: Solar priority, Utility priority, Solar, Utility & solar
- Utility or Battery output mode
- Display the system running status and data via LCD and indicator
- User & Engineer setting interface
- Convenient AC input breaker
- AC OUT button control AC output
- Battery temperature compensation function.
- Extensive Electronic protection

CE RoHS

Model	UP1500-M3222	UP2000-M3322	UP3000-M3322	UP3000-M2142
Nominal battery voltage	24V			48V
Input voltage range	21.6~32V			43.2~64V
Output voltage	220VAC/230VAC±3%			
Max. PV open circuit voltage	100V(-20℃); 92V(25℃)			150V(-20℃);138V(25℃)
Max. PV input power	520W	780W	7800W	1040W
Temp. compensation	-3mV/℃/2V (默认)			
Dimension	386×300×126mm	444×300×126mm		
Net weight	7kg	8.5kg	9kg	
Enclosure	IP30			
Working environment	-20℃~ +55℃			

SHI series

Pure sine wave inverter

400VA, 600VA, 1000VA 12V/24V/48V



SHI series is a pure sine wave inverter which can convert 12/24/48Vdc to 220/230Vac 50/60Hz based on full digital and intelligent design. It features high reliability, high efficiency, concise outline, small volume, easy installation and operation. The inverter can be applied in many fields, such as household appliances, electric tools and industrial devices etc, especially for solar photovoltaic power system.

Features:

- Input & output fully isolation
- Adoption of advanced SPWM technology, pure sine wave output
- Dynamic current loop control technology to ensure inverter reliable operation
- Wide DC input voltage range
- The output voltage and frequency can be switched
- Low output harmonic distortion (THD≤3%)
- LED indicators for input voltage range, load power range, normal output & failure state
- Optional energy saving mode
- Wide working temperature range (industrial level)
- Continuous operation at full power

CE RoHS IEC62109

Model	SHI400-12	SHI400-22	SHI600-12	SHI600-22	SHI1000-22	SHI1000-42	SHI2000-22	SHI2000-42	SHI3000-22	SHI3000-42
Nominal system voltage	12V	24V	12V	24V	24V	48V	24V	48V	24V	48V
Input voltage range	10.8~16Vdc	21.6~32Vdc	10.8~16Vdc	21.6~32Vdc	21.6~32Vdc	43.2~64Vdc	21.6~32Vdc	43.2~64Vdc	21.6~32Vdc	43.2~64Vdc
No Load Current	≤0.8A	≤0.45A	≤0.7A	≤0.45A	≤0.45A	≤0.35A	≤0.7A	≤0.7A	≤1.2A	≤1.0A
Output Voltage	220Vac±3% / 230Vac±10%									
Frequency	50/60Hz±0.2%									
Continuous power	400W		600W		1000W		2000W		3000W	
Surge power	900W		1350W		2250W		4600W		6900W	
Max. efficiency	≥92%	≥93%	≥93%	≥94%	≥94%	≥94%	≥95%	≥95%	≥95%	≥95%
Overall dimension	280×166×74.3mm		295×186×82mm		295×208×98mm		436×249×116mm		507×249×116mm	
Net weight	1.8kg		2.3kg		3.3kg		6.0kg		7.5kg	
Working temperature	-20℃~+50℃									
Relative humidity	≤95% (N.C.)									



STI series

Pure sine wave inverter

200VA,300VA,500VA,700VA,1000VA 12V/24V/48V

STI series is a sine wave power frequency inverter which can convert 12V/24V/48Vdc to 220V/230V 50Hz based on full digital and intelligent design. It features high reliability, high efficiency, concise outline, full protection functions, easy installation and operation. The inverter can be applied in many fields especially for solar photovoltaic power system.

Features:

- Complete isolation-type inverter technology, noiseless output
- Adoption of advanced SPWM technology, pure sine wave output
- Dynamic current loop control technology to ensure inverter reliable operation
- Wide DC input voltage range
- Excellent EMC design
- Low output harmonic distortion (THD≤3%)
- LED indicators for input voltage range, load power range, normal output & failure state
- Optional energy saving mode
- Wide working temperature range (industrial level)
- Continuous operation at full power

CE RoHS

Model	STI200-12-220	STI200-24-220	STI300-12-220	STI300-24-220	STI500-12-220	STI500-24-220	STI700-24-220	STI1000-24-220	STI1000-48-220
	STI200-12-230	STI200-24-230	STI300-12-230	STI300-24-230	STI500-12-230	STI500-24-230	STI700-24-230	STI1000-24-230	STI1000-48-230
Nominal system voltage	12V	24V	12V	24V	12V	24V	24V	24V	48V
Input voltage range	10.5~16V	21~32V	10.5~16V	21~32V	10.5~16V	21~32V	21~32V	21~32V	42~64V
Consumption no load(ON)	≤4W	≤5W	≤5W	≤6W	≤5W	≤6W	≤8.5W	≤10W	≤12W
Output voltage/Frequency	AC220V/230V±3% / 50Hz±0.2%								
Continuous power	200VA		300VA		500VA		700VA	1000VA	
Surge power	640VA		960VA		1600VA		2240VA	3200VA	
Max. efficiency	≥88%	≥89%	≥90%	≥91%	≥91%	≥93%	≥93%	≥93%	≥94%
Overall dimension	315*166*101mm				325*187*112mm		335×232×12 3.3mm	373×232×123.3mm	
Net weight	4.5kg		5.3kg		7.3kg		9.4kg	11.8kg	
Working temperature	-20℃ ~ +50℃								
Relative humidity	≤95% (N.C.)								

NEW

EPE series

Portable DC system




Portable DC system is designed for solar energy independent power supply machine. Unified Integration effectively ensure that the controller, solar panels, batteries and other major devices match highly, to ensure system of high performance and compatibility.

Easy to carry, beautiful and practical, customizable according to needs. Suitable for a variety of application scenarios, meeting the daily life and travel in the DC power supply needs.

Features:

- 2000 cycles rechargeable lithium battery, long service life
- Endurance strong, series of products power are more than 150Wh, can guarantee the user's daily lighting and US charging required.
- Controller configuration MPPT controller, 99% tracking efficiency, 98% conversion efficiency, shorten the time charging battery fully to ensure the stability of the load work.
- The system adopts low power consumption industrial design, Self-consumption 10mA, greatly improve the system power supply performance.
- Solar panels with high efficiency monocrystalline silicon PV cells; conversion efficiency $\geq 17\%$, 10 years of light failure $\leq 10\%$, foldable, easy to carry.
- Chassis-style clever design, fine craft production, compact structure, small size, light weight.

Model: EPE-1240DBL				
Picture	System components	Spec		
	PV array (Mono)	17.5V/40Wp		
	LiFePO4	12V/12AH		
	Solar charge controller	12V/5A		
	Output	USB output: 5V/2.4A		Qty: 2 pcs
		DC output: 12V/1A		Qty: 2 pcs
	Charging Mode	MPPT		
	Dimension	86.4*151.5*177.5mm	PV panel dimension	350*670*25mmx2 (folded)
	Weight	3kg	PV panel Weight	6.4kg
Item	Accessories			
1	LED lamp	12V/5W		
2	Lamp cables	4m		
3	Charging cables	5V/several connectors		





Solar Charge Controller • Inverter



Head Office

Beijing EPsolar Technology CO.,LTD.

Address: BLDG #18, CO.PARK ,NO.8 HEYING ROAD
,CHANGPING DISTRICT, BEIJING, CHINA 102200

Website: www.epsolarpv.com, www.epever.com

Tel: 86-10-82894112 / 82894962 / 82894528

Fax: 86-10-82894882

E-mail: info@epsolarpv.com

Branch Office

Beijing EPsolar Technology CO., LTD. Shenzhen Branch

Address: BLDG.A3, NO.18, FOUTH INDUSTRIAL PARK,
ZHULONGTIAN ROAD, SHUITIAN COMMUNITY, SHIYAN
STREET, BAOAN DISTRICT, SHENZHEN, GUANDONG
PROVINCE, CHINA, 518108.

Tel: 86-755-36863655

Fax: 86-755-36863665